

# Packaging for Damaged, Defective and Recalled Batteries and Devices

## The CellSafe® Envelope Kit



Cost Savings + Incredible Protection in One Neat Little Package.



DOT SPECIAL PERMIT 20910



CA EQUIVALENCY CERTIFICATE SU 13920

The CellSafe® Battery Envelope Kit offers engineered protection from thermal runaways in a thin textile envelope. Perfect for consumer recalls, the reusable aspect of the envelope contributes to cost savings.

- **Green** and **reusable** packaging as part of your supply chain. The textile envelope may be reused numerous times throughout a volume recall. Only the outer box will need to be replaced.
- Rapid customization program to accommodate unique size and shape of tools, appliances and personal devices.
- DOT Special Permit 20910 and Equivalency Certificate SU 13920 authorized.
- **P911** and **P908** tested and compliant.
- Proprietary high-performance composite envelope has been 14 CFR tested and rated for 2000°F for 30+ minutes.

### Simple Implementation

- No Hazmat Code of Federal Regulation (CFR) training required.
- Seamless integration and logistics with strategic battery recycling and recovery partners.
- Customized training/guide for personnel.
- Available in four standard sizes to accommodate laptops, tablets, phones, and other personal devices.
- Customize to accommodate batteries up to 185 Wh with nimble package prototyping and certification.

The Safest Reusable Recall Packaging on the Planet. Perfect for Warranty Returns and Reverse Logistics.

| SKU        | Box  | Textile Envelope               | UN Mark              | Tare Wt.            | Gross Weight*        |
|------------|--|--------------------------------|----------------------|---------------------|----------------------|
| CSENKT0811 | 12.3" x 8.6" x 1.4"<br>31cm x 22cm x 3.5cm   | 12" x 8.3"<br>30.5cm x 21cm    | 4G/X3/S/**/USA/M6484 | 0.45 lbs<br>0.2 kg  | Max. 6.6 lbs<br>3kg  |
| CSENKT0715 | 15.3" x 7.3" x 1.4"<br>39cm x 18.5cm x 3.5cm   | 15" x 7"<br>38cm x 18cm        | 4G/X3/S/**/USA/M6484 | 0.5 lbs<br>0.22 kg  | Max. 6.6 lbs<br>3kg  |
| CSENKT01   | 15.3" x 12" x 1.4"<br>39cm x 30.5cm x 3.5cm  | 15" x 11.5"<br>37.5cm x 29cm   | 4G/X5/S/**/USA/M6484 | 0.7 lbs<br>0.3 kg   | Max. 11 lbs<br>5kg   |
| CSENKT1216 | 17" x 12.3" x 1.4"<br>43.2cm x 31cm x 3.5cm  | 16.8" x 12"<br>42.7cm x 30.5cm | 4G/X6/S/**/USA/M6484 | 0.75 lbs<br>0.34 kg | Max. 13.2 lbs<br>6kg |
| CUSTOM     | Box and envelope size can be customized to your application with rapid package prototyping and certification |                                |                      |                     |                      |

\* Allowed total weight of package and contents \*\* Year of Manufacture

CSENKTv1.050123